



泛光灯系列/FLOOD LIGHT SERIES



DP1007

输入电压 / Input voltage (V): AC110-240
 频率 / Frequency (Hz): 50-60
 功率因数 / Power factor: ≥ 0.96
 色温 / Color temp. (K): 2700-7000
 显色指数 / CRI: $Ra \geq 75$
 光束角 / Beam angle: 120°
 工作温度 / Working temp. (°C): -20~50
 工作湿度 / Working humidity (%): 10-90
 IP防护等级 / IP class: IP65

LED Series

DAPU

ELECTRICAL CO., LTD.

Tel: 86-576-86402688
 Fax: 86-576-86402689
<http://m.cens.com/s/dapu>

Zhejiang DAPU Electrical Co., Ltd. is located in Wenling, Zhejiang province which is a developed city for light industry. Founded in 2002 with a registered capital of RMB 5 million, Zhejiang DAPU has focused on manufacturing in lighting components, like ballasts, transformers, gear-boxes and so on.



FL 15-30W
 Shape: 34x41mm/11(Medell H)

- ◆ Vacuum-impregnated coating
- ◆ Conforms to EN61347-1, EN61347-2-8
- ◆ Protection class I
- ◆ Screw connectors 0.75~2.5MM²



泛光灯系列/FLOOD LIGHT SERIES



DP1007

输入电压 / Input voltage (V): AC110-240
 频率 / Frequency (Hz): 50-60
 功率因数 / Power factor: ≥ 0.96
 色温 / Color temp. (K): 2700-7000
 显色指数 / CRI: $Ra \geq 75$
 光束角 / Beam angle: 120°
 工作温度 / Working temp. (°C): -20~50
 工作湿度 / Working humidity (%): 10-90
 IP防护等级 / IP class: IP65

Inductive ballasts

Gear-box

LED Series