

GB-T8x-x-x



- ◎ LED Type : Everlight
- ◎ Voltage : 110 ~ 240V AC
- ◎ Beam Angle : 120°
- ◎ Average Life Hour : > 30,000 Hours

◎ Color Description

Color	Lamp Shade	Length (Foot)	Product Number	Luminous Flux (lm)	Color Tem (K) Or Wavelength (nm)	Power Consumption (W)	Dimension
White	Clear	1	GB-T8C-1-W	450	6000K	4	26 x 345 mm
		2	GB-T8C-2-W	900		10	26 x 580 mm
		4	GB-T8C-4-W	1800		20	26 x 1210 mm
	Diffuse	1	GB-T8W-1-W	350		4	26 x 345 mm
		2	GB-T8W-2-W	700		10	26 x 580 mm
		4	GB-T8W-4-W	1400		20	26 x 1210 mm
Warm White	Clear	1	GB-T8C-1-M	350	3000K	4	26 x 345 mm
		2	GB-T8C-2-M	700		10	26 x 580 mm
		4	GB-T8C-4-M	1400		20	26 x 1210 mm
	Diffuse	1	GB-T8W-1-M	300		4	26 x 345 mm
		2	GB-T8W-2-M	550		10	26 x 580 mm
		4	GB-T8W-4-M	1200		20	26 x 1210 mm

• Contrast

Type	Brightness @1m (Typ)
GB-T802W120	250
60cm Fluorescent-lamp	200

© Apply to cardinal or assistance lighting also can use all several of outside or indoor places.

© Feature :

1. Easy Installation.
2. No UV or IR radiation.

©Note: Please make sure you remove the ballast and igniter in the existing fixing bracket, which may overdrive the LED tube when starting and underdrive it afterwards.

