



E SELF-DRIVING NUT

DIMENSIONS & SPECIFICATION								(MILLIMETERS)	
THREAD SIZE	P/N.	A	D ±0.015	L ±0.3	C	d	THREAD DEPTH NIN	HOLE SIZE ±0.1	
M6PH1.0	ESNM612	14mm	7.8mm	12mm	5mm	9.6mm	8mm	8.1mm	
	ESNM616	14mm	7.8mm	16mm	5mm	9.6mm	12mm	8.1mm	
	ESNM620	14mm	7.8mm	20mm	5mm	9.6mm	16mm	8.1mm	
	ESNM624	14mm	7.8mm	24mm	5mm	9.6mm	20mm	8.1mm	
M8PH1.0	ESNM812	17mm	9.45mm	12mm	5mm	11.25mm	8mm	9.75mm	
	ESNM816	17mm	9.45mm	16mm	5mm	11.25mm	12mm	9.75mm	
	ESNM820	17mm	9.45mm	20mm	5mm	11.25mm	16mm	9.75mm	
	ESNM824	17mm	9.45mm	24mm	5mm	11.25mm	20mm	9.75mm	
DIMENSIONS&SPECIFICATION								(INCH)	
THREAD SIZE	P/N.	A	D ±0.006	L ±0.012	C	d	THREAD DEPTH NIN	HOLE SIZE ±0.003	
1/4-20	ESNI612	0.563"	0.308"	0.5"	0.197"	0.378"	0.34"	0.311"	
	ESNI616	0.563"	0.308"	0.625"	0.197"	0.378"	0.47"	0.311"	
	ESNI620	0.563"	0.308"	0.75"	0.197"	0.378"	0.59"	0.311"	
	ESNI624	0.563"	0.308"	1"	0.197"	0.378"	0.84"	0.311"	
5/16-18	ESNI812	0.687"	0.375"	0.47"	0.197"	0.445"	0.31"	0.378"	
	ESNI816	0.687"	0.375"	0.63"	0.197"	0.445"	0.47"	0.378"	
	ESNI820	0.687"	0.375"	0.78"	0.197"	0.445"	0.62"	0.378"	
	ESNI824	0.687"	0.375"	0.94"	0.197"	0.445"	0.78"	0.378"	