

SPEED PIN RIVETS

5/32" DIAMETER	PART NUMBER	(L) LENGTH		GRIP RANGE (G)					
		(INCH)	(MM)	NOM.		MIN.		MAN.	
				(INCH)	(MM)	(INCH)	(MM)	(INCH)	(MM)
UNIVERSAL HEAD	TSP4.0S-1	0.250	6.350	0.125	3.175	0.109	2.769	0.141	3.581
	TSP4.0S-2	0.281	7.137	0.156	3.962	0.141	3.581	0.172	4.369
	TSP4.0S-3	0.312	7.925	0.188	4.775	0.172	4.369	0.203	5.156
	TSP4.0S-4	0.344	8.738	0.219	5.563	0.203	5.156	0.235	5.969
	TSP4.0S-5	0.375	9.525	0.250	6.350	0.235	5.969	0.266	6.756
	TSP4.0S-6	0.406	10.312	0.281	7.137	0.266	6.756	0.297	7.544
	TSP4.0S-7	0.437	11.100	0.312	7.925	0.297	7.544	0.328	8.331
	TSP4.0S-8	0.469	11.913	0.344	8.738	0.328	8.331	0.360	9.144
	TSP4.0S-9	0.531	13.487	0.406	10.312	0.391	9.931	0.422	10.719
	TSP4.0S-10	0.562	14.275	0.437	11.100	0.422	10.719	0.453	11.506
	TSP4.0S-11	0.625	15.875	0.500	12.700	0.484	12.294	0.515	13.081
	TSP4.0S-12	0.656	16.662	0.531	13.487	0.515	13.081	0.546	13.868
	TSP4.0S-13	0.687	17.450	0.562	14.275	0.546	13.868	0.578	14.681
	TSP4.0S-14	0.750	19.050	0.625	15.875	0.609	15.469	0.640	16.256
COUNTERSUNK HEAD	TSP4.0C-1	0.250	6.350	0.125	3.175	0.109	2.769	0.141	3.581
	TSP4.0C-2	0.281	7.137	0.156	3.962	0.141	3.581	0.172	4.369
	TSP4.0C-3	0.312	7.925	0.188	4.775	0.172	4.369	0.203	5.156
	TSP4.0C-4	0.344	8.712	0.219	5.563	0.203	5.156	0.235	5.969
	TSP4.0C-5	0.375	9.525	0.250	6.350	0.235	5.969	0.266	6.756
	TSP4.0C-6	0.406	10.312	0.281	7.137	0.266	6.756	0.297	7.544
	TSP4.0C-7	0.437	11.100	0.312	7.925	0.297	7.544	0.328	8.331
	TSP4.0C-8	0.469	11.913	0.343	8.712	0.328	8.331	0.360	9.144
	TSP4.0C-9	0.500	12.700	0.375	9.525	0.360	9.144	0.391	9.931
	TSP4.0C-10	0.531	13.487	0.406	10.312	0.391	9.931	.422	10.719