

# 光 美 光 電 有 限 公 司

LASIC ELECTRO-OPTICS CO., LTD

70955 台灣台南市安南區鹽田路30巷60號(科工區)

No. 60, Lane 30, Yantian Rd., Annan District, Tainan City, 70955, Taiwan.

TEL:+886-6-3841798 FAX:+886-6-3841800 Website:www.lasic.com.tw



## 工業用 雷射標點儀---規格表 Industrial-Use LASER POINTER KML - 3000P SERIES 系列

型 號 Model	KML-3501P	KML-3502P
光 源 Source	雷 射 二 極 體 Laser Diode	
波 長 Wavelength	630 ~ 650 nm	
輸出功率 Output Power	1mW	2mW
投射距離 Project Distance	1M / 2M / 3M	
標點直徑 Point Dia.	1.0mm / 2.0mm / 3.0mm (可調焦距) Focus Adjustable	
輸入電壓 Input Voltage	AC 90 ~ 260V to DC 5V Adaptor (PS1) or PS3 or PS5	
操作溫度 Operating Temp.	- 10 ~ 50 °C	
安全等級 Safety Class	Class III a	
使用壽命 Lifetimes	>15,000 小時(hr)	
外觀尺寸 Dimensions	D20×L72(mm)	
重 量 Weight	50 ± 5 公克 ( g )	
適用行業 Applications	<ul style="list-style-type: none"> <li>● PCB加工 PCB Processing</li> <li>● 光軸校準 Axis calibration</li> <li>● 基準點定位 Reference point for positioning</li> <li>● 鋼材鑽孔定位 Steel drillong location</li> <li>● 鈕釦鉚合加工 Buttons riveting process</li> <li>● 木材打釘加工 Fixing timber processing</li> </ul>	
備 註 Remarks	<p>1. 若未使用原廠設計之完整腳座固定雷射頭時,建議使用非金屬材質(如:塑鋼、電木),以隔絕雷射頭與機械設備的電位接觸。 If you do not use the original design of a complete mounting fixed to the laser head, recommend the use of non-metallic materials (such as: Plastic and bakelite), in order to cut off the laser head and the equipment conductive contact.</p> <p>2. 雷射光對人體眼睛的視網膜會造成傷害,使用操作時請勿直視光源。 Do not catch your sight with the beam. It may result in the harm to your eyes.</p>	