

INT-3000W-220



<b>Power ( W)</b>	<b>3000W</b>	
<b>Input Vdc</b>	<b>12Vdc</b>	<b>24Vdc</b>
<b>Output power continuous</b>	<b>3000w</b>	<b>3000w</b>
<b>AC output voltage</b>	<b>220 or 230 or 240Vdc</b>	
<b>Regulation( ±5%)</b>	<b>±5%</b>	<b>±5%</b>
<b>Output waveform</b>	<b>Ture sine wave</b>	<b>Ture sine wave</b>
<b>DC input voltage</b>	<b>10-15Vdc</b>	<b>20-30Vdc</b>
<b>Frequency (±2Hz)</b>	<b>50 or 55 or 60Hz</b>	<b>50 or 55 or 60Hz</b>
<b>Efficiency</b>	<b>&gt;85%</b>	<b>&gt;85%</b>
<b>No load current draw</b>	<b>&lt;2.0A</b>	<b>&lt;1.5A</b>
<b>Thermal protection</b>	<b>60±10℃</b>	<b>60±10℃</b>
<b>Cooling fan</b>	<b>YES</b>	<b>YES</b>
<b>Short protection</b>	<b>YES</b>	<b>YES</b>
<b>Overload protection</b>	<b>YES</b>	<b>YES</b>
<b>Low battery alarm</b>	<b>10.5 ± 0.5Vdc</b>	<b>21 ±1Vdc</b>
<b>Low battery Shutdown</b>	<b>10 ± 0.5Vdc</b>	<b>20 ± 1Vdc</b>
<b>High battery shutdown</b>	<b>15 ± 0.5Vdc</b>	<b>32 ± 1Vdc</b>
<b>Battery polarity reverse(by fuse)</b>	<b>YES</b>	<b>YES</b>
<b>Fuse</b>	<b>35A * 10pcs</b>	<b>20A * 10pcs</b>
<b>Operating environment temperature</b>	<b>-15℃ to + 50℃</b>	<b>-15℃ to + 50℃</b>
<b>Dimensions(LxWxH)</b>	<b>480 x 289 x 100mm</b>	<b>480 x 289 x 100mm</b>
<b>Net weight</b>	<b>9500g</b>	<b>9500g</b>