

650 S-TYPE Specification

ENGINE :		
4 Cycle Gasoline -- Made in Japan (Oil-Type Air Filter)		
Type :	GM182 : 6 HP / 1800 rpm Mitsubishi	Engine Weight : 16 KG
	GX200 : 6.5HP / 1800 rpm Honda	Engine Weight : 16 KG
Ignition : Electronic		
Start Mode : Recoil Starter		
Fuel Tank : 3.6 liter		
The Device :		
Gearshift Mode	Direct shifting-gear drive for 2 forward / 2 reverse movement	
Transmission	Belt / Tension wheel drive	
Speed	Forward	High Speed : 2.82
	(km/hr)	Low Speed : 1.49
	Backward	High Speed : 3.94
	(km/hr)	Low Speed : 2.08
Tillage part	Rotary speed of the tillage blade (including the secondary gear-change)	1 / 486 2 / 263
		3 / 414 4 / 224
Adjustable Tread	Narrowest : 18cm	
	Widest : 36cm	
Tire Specification	350-5 herringbone design	

Tillage	Depth (cm)	3-25
	Width (cm)	65
Banking up	Ditch Depth (cm)	3-30
	Ditch Width (cm)	18、 24、 30、 36、 45
Dimension (L x W x H)	145 x 65 x 85 (cm)	
Adjustable Handle	5-section height adjustment	
Net Weight	110kg (including 6-rotary tillage blade , excluding the engine)	