

# 650 G-TYPE Specification

## ENGINE :

4 Cycle Gasoline -- Made in Japan (Oil-Type Air Filter)

Type : GB180 : 6.3 HP / 1800 rpm Mitsubishi Engine Weight : 16 KG

GX200 : 6.5 HP / 1800 rpm Honda Engine Weight : 16 KG

Ignition : Electronic

Start Mode : Recoil Starter

Fuel Tank : 3.6 liter

## The Device :

Gearshift Mode	Direct shifting-gear drive for 2 forward / 2 reverse movement	
Transmission	Belt / Tension wheel drive	
Speed	Forward	High Speed : 2.82
	(km/hr)	Low Speed : 1.49
	Backward	High Speed : 3.94
	(km/hr)	Low Speed : 2.08
Tillage part	Maximum rotary speed of the tillage blade (2-speed gear-change)	440rpm
Adjustable Tread	Narrowest : 15cm , Widest : 33cm	
Tire Specification	350-5 herringbone design	

Tillage	Depth (cm)	3-25
	Width (cm)	46
Banking up	Ditch Depth (cm)	3-30
	Ditch Width (cm)	16
Dimension ( L x W x H )	145 x 65 x 85 (cm)	
Adjustable Handle	5-section height adjustment	
Net Weight	100kg (including 4-rotary tillage blade)	