

Powerful Myday Chucker



STANDARD ACCESSORIES:

Controller: FANUC, FAGOR or SIEMENS
 AC spindle motor
 Auto lubrication system
 Coolant system
 Spindle Oil Chiller
 Electric Cabinet Air Conditioner
 Splash guard
 Work light
 Leveling bolts & pads
 Chip conveyor

OPTIONAL ACCESSORIES:

3-Jaw Chuck
 4-Jaw Chuck
 Hydraulic Chuck (front chuck only)
 Pneumatic Chuck
 Double Chuck System
 Hydraulic 4-way Toolpost
 Servo H6 Turret
 Servo H8 Turret



Description \ Model	PMC-9	PMC-10	PMC-12	PMC-14	PMC-21
Spindle bore	Ø230mm (9")	Ø260mm (10")	Ø310mm (12")	Ø360mm (14")	Ø535mm (21")
Spindle nose	A2-15	A2-15	A2-20	A2-20	A2-28
Spindle speeds (4 Steps)	4-600	4-540	3-400	3-360	2-300
Swing over bed	1200 mm				
Swing over cross slide	740 mm				
Bed width	800mm (32")				
Spindle motor	30KW		37KW		
Cutting speed	X-axis : 0~5 m/min , Z-axis : 0~5 m/min				
Max, x-axis travel	600mm				
Max, z-axis travel	1500 mm				
Ball screw	X: Ø50xP10; Z: Ø80xP10				
Controller	FAGOR 8055i	FANUC 0i-TD		SIEMENS 828D	
X-axis servo motor	FKM 66	α22i		1FK7101	
Servo motor output ※	4.9 KW	4.0 KW		4.8 KW	
Z-axis servo motor	FKM 66	α22i		1FK7101	
Servo motor output ※	4.9 KW	4.0 KW		4.8 KW	
Coolant pump motor	1HP				
※ Our design enhances output torque					



台秀
MYDAY

MYDAY MACHINERY INC

No.112-53, Cingguang Rd., Wurih District,

Taichung City 41462, Taiwan, R.O.C.

TEL:+886-4-23351313 FAX:+886-4-23352259

Email: mydayche@ms61.hinet.net

Website: <http://www.my-day.com.tw>