



## Lutér Fire Command Rim Type and Fire Exit Device ANSI A156.3, Grade 1

**Model No. #5500**

### Specifications

#### For Doors

1 3/4" thick standard, optional 2 1/4" Thick. 4 1/2" minimum stile width required for single or double door application using standard 239 strike and pull or lever trims.

#### Chassis

Nonferrous alloy (Panic Grade), steel (Fire Grade).



#### Cover

Drawn stainless steel, steel, or brass.

#### Mounting

Furnished standard with machine screws. Available with thru bolts on request.

#### End Cap

Steel construction.

UL and ULC Listed...5500 Series for panic.  
conforms to standards UL 10C and UBC 7-2-1997 codes.

#### Door Size

32" / 36" / 48"

#### Finish

Description	BHMA	US Finish	Material
Primecoat / /	600	SUP	Steel
Polished Brass, Clear Powder Coat	605	US3	Brass
Satin Brass, Clear Powder Coat	606	US4	Brass
Polished Bright Bronze	611	US9	Bronze
Satin Bronze Clear Powder Coat	612	US10	Bronze
Oiled Rubbed Bronze	613	US10B	Bronze or steel
Polished Bright Chrome	625	US26	Brass or steel
Satin Chrome	626	US26D	Brass or steel
Polished Bright Stainless	628	US32	Stainless Steel
Satin Stainless	630	US32D	Stainless Steel